

reVER

energy solutions



200kWh - 400kWh capaciteit
2x90kW - 1x180kW Vermogen

CESS-MOBIEL

Productspecificaties



CESS-MOBIEL

Technische Data		
Batterij Systeem Batterij		
Capaciteit Batterij	200kWh	400kWh
spanning Max. laad-	653V	
stroom EV-lader(s)	200A	300A
Uitgang Spanning CCS DC-		
Ingang EV-herlaad modus	2x 90kW of 1x 180kW CCS stekker	
AC Uitgangen CEE	200~1.000Vdc	
connectors AC grid laden		
CEE connector Overige	Via optionele 200A CCS laad-unit	
parameters Operationele		
temperatuur Bescherming	1x 220Vac-16A, 2x 63A – 3P/400V, 1x 125A-3P/400V	
Aantal cycli Temperatuur		
management HMI Display	1x 63A 3P/400V	
Behuizing Anti corrosie		
bescherming Afmetingen	-10 ~ 50°C	
(LxBxH) Gewicht	IP65	
	>4.500 cycli, 90% DoD, >75% EOL	
	Vloeistof gekoeld batterijen, geforceerde luchtkoeling voor de converters	
	10" LCD scherm	
	Plaatstaal	
	C4	
	2300x1500x1300mm	2300x1500x1900mm
	2.200kg	3.950kg

rever
energy solutions

Rever Energy Solutions

☎ Telefoon: +31(0)13 2106 725

✉ E-mail: info@reverenergy.nl

🌐 Website: reverenergy.nl

